

Powerful. Beautiful.  
**Excellence · Innovation**

PI21185  
PI22185  
PI24185



## Shanghai Panelmate Electronics Co., Ltd.

18.5" WXGA Raspberry Panel PC






## Features

- Display type: 10.1", 10.4", 11.6", 12.1", 12.2", 15", 15.6", 17", 17.3", 18.5", 19", 21.5", 24", 27"
- Front panel/back cover: Aluminium-magnesium alloy
- Front panel/Rear: IP65 / IP20
- Screen Type: Single point resistive touchscreen, Multi-point capacitive touchscreen, Non-touch screen
- Built-in UPS power supply
- RTC real-time clock
- OS: LINUX or Raspberry PI
- Interface: HDMI, Type-C, 4xUSB and 2xCAN
- DC 24V


## Namely Rule



## Specifications


Model	PI21185&PI22185&PI24185	
<b>Processor</b>	CPU	Broadcom BCM2711 1.5 GHz,64-bit,4 cores,ARM Cortex-A72
	Memory	2G (Deafult) /4G/8G
	Storage	8G eMMC (Deafult) /16G/32G eMMC
<b>I/O</b>	LAN	1 x 1000Mbps, BCM54210PE; 1 x 100Mbps, SR9900AI
	USB	1 x Micro USB, 4 x USB 2.0
	CAN	2 x CAN
	Display Port	HDMI
<b>Power</b>	Input Voltage	DC 24V
	Power	26W
<b>Physical</b>	Dimension (WxHxD/mm)	463 x 303 x 57.5 ( 18.23" x 11.93" x 2.26" )
	Open Size (WxH/mm)	452 x 292 ( 17.80" x 11.50" )
	Net Weight(kg)	4.45kg
	Mounting	Embedded,Wall-mounted,Desktop,VESA
<b>LCD</b>	Display Type	18.5" WXGA TFT
	Resolution	1366 x 768
	Colors	16.7M
	Active Area (WxH/mm)	409.8 x 230.4 ( 16.13" x 9.07" )
	Backlight	LED
	MTBF (hour)	30000hrs
	Pixel Pitch (HxV)	0.3 x 0.3
	Luminance(cd/m2)	250cd/m2
	Contrast Ratio	1000:1
	Viewing Angle	(L)89 / (R)89 / (U)89 / (D)89
<b>Touchscreen</b>	Touch Type	Single point resistive touchscreen & Multi-point capacitive touchscreen & Non-touch screen
	Light Transmission	>85%
	Controller	USB interface
	Driver Support	Ubuntu, Ubuntu Mate
	Multi-touch	10 points (LINUX)
	Surface Hardness	Resistive touchscreen: Mohs' Number>= 3H; Capacitive touchscreen: Mohs' Number 7H
<b>Environment</b>	Operating Temperature	0 ~ 50°C
	Storage Temperature	-20 ~ 60°C
	Relative Humidity	5~95% ( Non condensation )
	Shock	Operating 10G peak acceleration(11 ms duration), follow IEC 60068-2-27
	Vibration	Operating Random Vibration Test 5~500Hz, 1Grms@with HDD; 2Grms@with SSD, follow IEC 60068-2-64
	EMC	CE/FCC Class A
	Front Panel Protection	IP65

## Technical Drawings unit: mm



Panel Cutout Dimensions: 452 x 292mm ( 17.80 x 11.50in )

## External I/O View



Interface definition:

- A: DC IN
- B: Micro USB
- C: HDMI
- D: 4 x USB2.0
- E: 2 x Ethernet LAN
- F: 2 x CAN

## Ordering Information

Part Number	Description
PI21185	18.5" TFT LCD / Resistive touch screen / DC 24V / Resolution 1366 x 768 / 2xLAN / 4 x USB / 1 x HDMI / 2 x CAN / 1 x Micro USB
PI22185	18.5" TFT LCD / Capacitive touch screen / DC 24V / Resolution 1366 x 768 / 2xLAN / 4 x USB / 1 x HDMI / 2 x CAN / 1 x Micro USB
PI24185	18.5" TFT LCD / Non-touch screen / DC 24V / Resolution 1366 x 768 / 2xLAN / 4 x USB / 1 x HDMI / 2 x CAN / 1 x Micro USB

## Packing List

Terminal	3pin spring clamp terminal
----------	----------------------------

Note: Package contents are subject to change without prior notice