

Powerful. Beautiful.
Excellence · Innovation

PI22240
PI24240



Shanghai Panelmate Electronics Co., Ltd.

24" FHD Raspberry Panel PC (Vertical Screen)




PI22240 (P) & PI24240 (P)



Features

- Display type: 10.1", 10.4", 11.6", 12.1", 12.2", 15", 15.6", 17", 17.3", 18.5", 19", 21.5", 24", 27"
- Front panel/back cover: Aluminium-magnesium alloy
- Front panel/Rear: IP65 / IP20
- Screen Type: Single point resistive touchscreen, Multi-point capacitive touchscreen, Non-touch screen
- Built-in UPS power supply
- RTC real-time clock
- OS: LINUX or Raspberry PI
- Interface: HDMI, Type-C, 4xUSB and 2xCAN
- DC 24V

Namely Rule




Specifications

Model	PI22240 & PI24240	
Processor	CPU	Broadcom BCM2711.1.5 GHz,64-bit,4 cores,ARM Cortex-A72
	Memory	2G (Deafult) /4G/8G
	Storage	8G eMMC (Deafult) /16G/32G eMMC
I/O	LAN	1 x 1000Mbps, BCM54210PE; 1 x 100Mbps, SR9900AI
	USB	1 x Micro USB, 4 x USB 2.0
	CAN	2 x CAN
	Display Port	HDMI
Power	Input Voltage	DC 24V
	Power	22W
Physical	Dimension (WxHxD/mm)	581.4 x 348.6 x 60 (22.89" x 13.72" x 2.36")
	Open Size (WxH/mm)	567 x 334 (22.32" x 13.15")
	Net Weight(kg)	6.5kg
	Mounting	Embedded,Wall-mounted,Desktop,VESA
LCD	Display Type	24" FHD TFT
	Resolution	1920 x 1080
	Colors	16.7M
	Active Area (WxH/mm)	527.04 x 296.46 (20.75" x 16.67")
	Backlight	LED
	MTBF (hour)	30000hrs
	Pixel Pitch (HxV)	0.2745 x 0.2745
	Luminance(cd/m2)	250cd/m2
	Contrast Ratio	3000:1
	Viewing Angle	(L)89 / (R)89 / (U)89 / (D)89
Touchscreen	Touch Type	Multi-point capacitive touchscreen & Non-touch screen
	Light Transmission	>85%
	Controller	USB interface
	Driver Support	Ubuntu, Ubuntu Mate
	Multi-touch	10 points (LINUX)
	Surface Hardness	Capacitive touchscreen: Mohs' Number 7H
Environment	Operating Temperature	-0 ~ 50°C
	Storage Temperature	-20 ~ 60°C
	Relative Humidity	5~95% (Non condensation)
	Shock	Operating 10G peak acceleration(11 ms duration), follow IEC 60068-2-27
	Vibration	Operating Random Vibration Test 5~500Hz, 1Grms@with HDD; 2Grms@with SSD, follow IEC 60068-2-64
	EMC	CE/FCC Class A
	Front Panel Protection	IP65


PI22240 (P) & PI24240 (P)

Technical Drawings unit:mm



Panel Cutout Dimensions: 567 x 334mm (22.32 x 13.15in)

External I/O View



Interface definition:

- A: DC IN
- B: Micro USB
- C: HDMI
- D: 4 x USB2.0
- E: 2 x Ethernet LAN
- F: 2 x CAN

Ordering Information

Part Number	Description
PI22240	24" TFT LCD / Capacitive touch screen / DC 24V / Resolution 1920 x 1080 / 2xLAN / 4 x USB / 1 x HDMI / 2 x CAN / 1 x Micro USB
PI24240	24" TFT LCD / Non-touch screen /DC 24V / Resolution 1920 x 1080 / 2xLAN / 4 x USB / 1 x HDMI / 2 x CAN / 1 x Micro USB

Packing List

Terminal	3pin spring clamp terminal
----------	----------------------------

Note: Package contents are subject to change without prior notice